



DuPont™ Krytox® Lubricants for the Power Generation Industry

DUPONT PERFORMANCE LUBRICANTS PROVIDES THE SOLUTION YOU NEED

Application	DuPont™ Krytox® Lubricant	Temperature Range (°F)	Temperature Range (°C)	ISO Viscosity	Properties
Coal Fired Power Plant					
Steam Turbine Governor	XHT-BDZ	-4 to 610	-20 to 320	500	High performance, extreme pressure and extreme high temperature anti-fretting grease.
Sootblower Carriage Bearings and Gears	GB Series	-40 to 535	-40 to 280	100–500	High temperature non-oxidizing grease designed to extend bearing, gear and seal life. Contact your DuPont representative for assistance in selection of the right product for your operating conditions.
Turbine Pedestal Thrust Bearing	Contact DuPont Representative	-22 to 625	-30 to 330	440–740	Contact your DuPont representative for assistance in selection of the right product for your operating conditions.
Hydro Grate Stoker	XHT-ACX	14 to 572	-10 to 300	680	Very high temperature grease. Safe around all chemicals. Won't wash out with water or solvents.
Damper Bearings	GPL 227	-22 to 550	-30 to 288	460	High temperature, long life, high load carrying, anti-corrosion grease.
Valves (Steam and other high temperature)	GPL 207	-22 to 550	-30 to 288	460	High temperature, long life grease.
Fan Bearings	GPL 226	-33 to 500	-36 to 260	220	High temperature, long life, high load carrying, anti-corrosion grease.
Natural Gas Fired Power Plant					
Gas Turbine Trunnion Bearing	XHT-BDZ	23 to 750	-5 to 399	1000	Extreme high temperature grease.
Nuclear Power Plant					
Steam Turbine Governor	XHT-BDZ	-4 to 610	-20 to 320	460	High performance, extreme pressure and extreme high temperature anti-fretting grease.
Fan Bearings	GPL 226	-33 to 500	-36 to 260	220	High temperature, long life, high load carrying, anti-corrosion grease.
Radiation Resistant Lubricant	EG 2000	-33 to 500	-36 to 260	220	High temperature, long life, low volatility grease.
General MRO Applications					
Switchgear electrical contact grease	EG 3000	-22 to 550	-30 to 288	460	High temperature, long life, low volatility grease.

DuPont Performance Lubricants

Extreme conditions. Extreme performance.

For more information or for technical assistance, please call **1-800-424-7502** or contact us at **krytox@usa.dupont.com**

For international sales and support contacts, visit us at **www.lubricants.dupont.com**

Copyright © 2011 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™ and Krytox® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-16091-2 (03/11) Printed in the U.S.A.

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, DuPont makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents or trademarks.



The miracles of science™

Maahantuoja:

 **YTM-Industrial**
INDUTRADE GROUP

Petikontie 20, 01720 Vantaa
Puh. 029 006 230, fax. 029 006 1230
www.ytm.fi, e-mail ytm.info@ytm.fi

Jälleenmyyjä: