



BIODEGRADABLE PRODUCTS



Precision Clean Multi-Purpose Cleaner/Degreaser

- Super industrial strength removes tough stains and soils
- Water-based
- Alkaline formula inhibits flash rusting
- pH concentrate = 13
pH ready-to-use = 12.5
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia or abrasives
- Rinses clean
- Safe on all surfaces except magnesium
- Three formulations available: Aerosol, Concentrate and Ready-to-use

NSF Nonfood Compounds Program
Listed Category Code: C1
Registration #059854

Product No.	Net Fill
Concentrate	
02701	1 gal. (3.78 l)
02705	5 gal. (18.93 l)
02755	55 gal. (208 l)

Product No.	Net Fill
Ready-to-Use	
02720	18 oz. (510 g) aerosol
02728	28 fl. oz. (828 ml) trigger
02765	55 gal. (208 l)



BFX All-Purpose Cleaner

- Water-based, butyl-free
- Rinses clean
- Non-corrosive
- pH 11 - 11.5
- Industrial strength for hard to remove dirt and oil
- Ideal for parts washers & pressure washers
- Safe on most surfaces except magnesium
- Value Performance



Nonfood Compounds Program
Listed Category Code: C1
Registration #130101

Product No.	Net Fill
05528	28 fl. oz. (828 ml) trigger
05501	1 gal. (3.78 l)
05505	5 gal. (18.93 l)
05555	55 gal. (208 l)



T-91 Non-Solvent Degreaser

- Contains no solvents
- Premium performance cleaning ability
- Zero VOCs; VOC's per CARB/OTC/LADCO: 0 g/L
VOC content per SCAQMD: 0 g/L
- "Green": Recognized by U.S. EPA's (Environmental Protection Agency) Design for the Environment (DfE) Requirements
- Non-flammable
- Non-toxic
- Low odor
- Proprietary formula
- Non-dilutable - Must be used straight
- Efficient: requires less product than traditional solvents to get the job done
- Ideal for basin style part washers and dip tanks
- Moderate foam for effective mechanical cleaning

Recognized for Safer Chemistry
www.epa.gov/dfe



Nonfood Compounds Program
Listed Category Code: A1
Registration #141975

Product No.	Net Fill
06301	1 gal. (3.78 l)
06305	5 gal. (18.93 l)
06355	55 gal. (208 l)

WorkPlace Orange Pumice Hand Cleaner

- Quickly removes the toughest soils
- Contains pumice for deep-cleaning strength
- Heavy-duty scrubbing pumice removes grease, grime, tar, ink, oil and paint
- Low VOCs per CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)
- Contains no harsh chemicals
- Fresh citrus scent



Product No.	Net Fill
09216	16 fl.oz. (473 ml)
09228	1 gal. (3.78l)

Tapmatic® Edge Cutting Fluids

- Excellent for high alloy metals
- Liquid-compatible with drop applicators
- Stick-excellent for lubricating band saw blades, grinding wheels and belts
- Creme-excellent for vertical applications
- Extends the life of cutting tools
- Water rinsable
- Can be used in cutting and forming operations on all metals
- Safe on all metals

Product No.	Net Fill
43020	16 fl. oz. (473 ml)
43030	1 gal. (3.78 l)
43200	13 oz. (364 g) stick
43100	10 fl. oz. (0.296 l) creme



ThermaPlex® BioGreen™ Bearing Grease

- Environmentally responsible, premium performance
- Non-toxic
- Prolongs bearing life, NLGI No. 2
- Outstanding extreme pressure (EP) performance
- EMCOR Rust Test, ASTM D6138 rating 0/0
- Multi-application bearing grease, exceptional water resistance
- Wide operating temperature range: -10°F-370°F (-23°C-188°C)

Product No.	Net Fill
70714	14.1 oz. (400 g) cartridge
70706	35 lbs. (5 gal.) pail



Nonfood Compounds Program
Listed Category Code: H2
Registration #142148

TechLube®-HD Heavy-Duty Cable Pulling Lubricant



- Water-based, gel lubricant
- Compatible with all types of cable jacket materials
- Will not "cement" the cable to the conduit
- Coats electrical utility & telecommunication cables
- Clings to cable and vertical placing applications
- Maintains a long-lasting lubricating film
- Nonflammable

Product No.	Net Fill	Product No.	Net Fill
Summer Grade	32°F (0°C) to 150°F (66°C)	Winter Grade	-15°F (-26°C) to 150°F (66°C)
61101	1 gal. (3.78 l)	61505	5 gal. (18.93 l)
61105	5 gal. (18.93 l)	Clear (Pulling Lubricant)	
61110	10-1/2 gal. Prelube bag	62633	32 fl. oz. bottle (946 ml)

Tapmatic® Natural Cutting Fluid

- Natural-based oils
- Non-toxic & non-hazardous
- Does not contain sulfur, chlorine, chlorinated solvents, water, mineral oil, or inactive fillers
- High performance lubricating ability eliminates galling and seizing
- Safe on all metals



Product No.	Net Fill
44220	16 fl. oz. (473 ml)
44230	1 gal. (3.78 l)
44240	5 gal. (18.93 l)
44260	55 gal. (208 l)

Power Pull Wire Pulling Lubricant

- Water-based lubricant
- Leaves a lubricating film that clings to cable during long pulls & vertical pulls
- Excellent for electrical applications
- Compatible with all types of cables & cable jacket materials
- Will not "cement" the cable to the conduit
- Worker safe
- Environmentally safe
- Can be applied by hand, brush or pump



Product No.	Net Fill
64432	32 fl. oz. (946 ml) bottle
64405	5 gal. (18.93 l)

TechLube®-FO Fiber Optic Cable Pulling Lubricant



- Nonflammable, water-based, gel lubricant
- Coats fiber optic cables and coaxial cables and for the installation of innerduct
- Compatible with all types of cable jackets, inner duct and conduit
- Will not "cement" the cable to the conduit
- Coats evenly and clings to the cable
- Provides maximum friction reduction for difficult long run cable pulling applications
- Maintains a long-lasting lubricating film

Product No.	Net Fill	Product No.	Net Fill
Summer Grade	32°F (0°C) to 150°F (66°C)	Winter Grade	-15°F (-26°C) to 150°F (66°C)
61701	1 gal. (3.78 l)	61801	1 gal. (3.78 l)
61725	2.5 gal. (9.46 l)	61825	2.5 gal. (9.46 l)
61705	5 gal. (18.93 l)		

Anti-Spatter

- Unique water-based formula that prevents weld spatter from sticking to metal
- Non-toxic, nonflammable
- Oversized, E-Z Spray Nozzle is ideal when wearing welding gloves

- Does not contain chlorinated solvents or silicone
- Paint compatible
- Eliminates the need for chiseling, grinding, or brushing after welding

Product No.	Net Fill
02116	13 oz. (368 g) aerosol

Internet Web Site: www.lpslabs.com

MAAHANTUOJA:

YTM-Industrial
INDUTRADE GROUP

Petikontie 20, 01720 Vantaa
Puh. 029 006 230, fax. 029 006 1230
www.ytm.fi, e-mail ytm.info@ytm.fi